

PRODUCT SPECIFICATION

THE GOODYEAR TIRE & RUBBER CO.
GOODYEAR CHEMICAL AKRON, OH 44306-3299
USA: 1-800-548-8107

POLYSTAY 100 PASTILLE

Description: POLYSTAY 100 PASTILLE is a mixture of diaryl -p-phenylenediamines.

PROPERTY	LIMITS	TEST METHOD
Appearance	blue-brown pastilles	Visual
Fineness through 3/8" screen,	100	NF-WI-0004
Total diaryl-p-phenylene diamines ,	>= 80	NF-WI-0010
RZ Total, %	==0	
Iron, ppm	<= 750	NF-WI-0002
Melting point, C,	97.0 +/- 4.0	NF-WI-0005
(DSC Peak Test)		ASTM D 1519
Purity, R1679Z, %	44.0 +/- 4	NF-WI-0010
Purity, R898Z, %	19.0 +/- 4	NF-WI-0010
Purity, R59Z, %	20.0 +/- 4	NF-WI-0010

This product should be stored in its original packaging in a dry atmosphere away from heat and ultraviolet light

As a guideline, POLYSTAY 100 PASTILLE should be re-tested every 36 months following the date of manufacture . The most appropriate test would be Assay .

Goodyear test methods are available upon request .

Check with your Goodyear salesperson to confirm the revision number of the most recent specification .

CD-PS-0701; Rev: (04/20/2010 12:00:00 AM) - POLYSTAY 100 PASTILLE

Print Date: 10/25/2010