

Technical Data Sheet

Biphenyl, Flake

Key Attributes

- High boiling point
- High chemical stability
- High flash point
- High solvency
- Low polarity
- Low reactivity

Product Description

Applications for biphenyl process fluid include process media or solvents in many industries, including chemicals and petrochemicals.

For more information, visit www.processfluid.com.

Typical Properties

Property	Test Method	Typical Value, Units
General		
Appearance		
Above 69°C (156°F)		Clear colorless liquid
Below 69°C (156°F)		White solid
Composition		Biphenyl
Molecular Weight (Average)		154
Density		
@ 25°C (77°F)		0.993 g/mL (8.27 lb/gal)
Flash Point	ASTM D92	113 °C (235 °F)
Water solubility		
@ 20°C (68°F)		Insoluble
Moisture Content		150 ppm, max
Autoignition Temperature	ASTM E659	540 °C (1004 °F)
Fire Point	ASTM D92	113 °C (235 °F)
Normal Boiling Point		255 °C (491 °F)
Vapor Pressure		
@ 166°C (330°F)		4.626 kPa (0.671 psia)

Comments

Values quoted are typical values obtained in the laboratory from production samples and are not guaranteed. Production materials may vary. Contact Eastman for current sales specifications.

Typical properties does not constitute an express warranty.

Eastman and its marketing affiliates shall not be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. No warranty is made of the merchantability of fitness of any product, and nothing herein waives any of the Seller's conditions of sale.

© 2018 Eastman Chemical Company or its subsidiaries. All rights reserved. As used herein, ® denotes registered trademark status in the U.S. only.