	SECTION 1: IDENTIFICAT	ION				
Trade Name & Synonyms	Sulfur, Pulverized Sulfur, Rubbermakers Sulfur, Commercial Sulfur					
Chemical Name	Sulfur					
CAS Number	7704-34-9	7704-34-9				
Family Name	Element – Sulfur	Element – Sulfur				
Chemical Formula	S ₈	S ₈				
Recommended Use	Rubber compounding and various industrial applications					
Restrictions on Use	None known. Keep away from heat sources, sparks, or open flames.					
Manufacturer/Supplier	Sales and Technical Services International Sulphur, Inc. P. O. Box 611 Mt. Pleasant, TX 75456 Tel: (903) 577-5500 Fax: (903) 577-5540 isulphur@internationalsulphur.com	Shipping and Receiving International Sulphur, Inc. 1386 North Frontage Road Mt. Pleasant, Texas 75455 Tel: (903) 577-5500 Fax: (903) 577-5540 GPS Coordinates: 33°9' 34″ N 95° 03' 29″ W				
Emergency Assistance	CHEMTREC Tel: (800) 424-9300 within the USA Tel: 001-703-527-3887 outside the USA					

SECTION 2: HAZARDS IDENTIFICATION

GHS Information:

Classification: Skin irritation, Category 3

OSHA Defined Hazards: Combustible dust

GHS Label Elements

Pictogram (s):



Signal Word: Warning

Hazard Statement: May cause skin irritation. May form combustible dust concentrations in air.

SECTION 2: HAZARDS IDENTIFICATION			
Hazard Statement	H303: May be harmful if swallowed.		
	H316: May cause mild skin irritation.		
	H320: May cause eye irritation.		
	H335: May cause respiratory irritation.		
Prevention Statement	P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.		
	P220: Keep away from oxidizing agents.		
	P242: Use non-sparking tools when available.		
	P243: Take precautionary measures against static discharge.		
	P261: Avoid breathing dust/fume/gas/mist/vapors/spray.		
	P264: Wash hands thoroughly after handling and before eating.		
	P284: In case of inadequate ventilation, wear respiratory protection.		
Response Statement	P362: Take off contaminated clothing.		
	P363: Wash contaminated clothing before reuse.		
	P370+P378: In case of a fire, use water fog, spray, or regular foam to		
	extinguish. Do not use a direct water stream.		
	P381: Eliminate all ignition sources.		
Storage Statement	P402: Store in a dry place.		
	P404: Store in a closed container.		

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Characterization

Mixture

Product	Percentage Contained	CAS Number	
Sulfur	>99.5%	7704-34-9	

Hazardous Ingredient None

	SECTION 4: FIRST AID MEASURES
Description of First Aid Measures	
Skin	Wash skin thoroughly with mild soap and water. Wash exposed clothing separately before reuse.
Еуе	Immediately flush eyes with plenty of water for 15 minutes, while holding upper and lower lid apart to insure rinsing of entire eye surface and lids. Do not use boric acid to rinse with. FOR SEVERE IRRITATION, SEEK MEDICAL ATTENTION, preferably an ophthalmologist
Inhalation	Move victim to fresh air. Watch for signs of an allergic reaction. Use a bronchodilator inhaler if directed by asthma patient. Keep victim warm and quiet. If not breathing, give artificial respiration. If heart has stopped beating, start cardiopulmonary resuscitation (CPR). SEEK MEDICAL ATTENTION.
Ingestion	Give one tablespoon of <i>Syrup of Ipecac</i> to induce vomiting. If vomiting does occur, give fluids again. If vomiting has not occurred in twenty minutes, the same dose of <i>Syrup of Ipecac</i> may be repeated one additional time. Alternatively, vomiting may be induced by touching the back of the throat with a finger. Do not give anything by mouth to an unconscious or convulsing person. SEEK MEDICAL ATTENTION.

SECTION 4: FIRST AID MEASURES (CONT)

Most Important Symptoms and Effects (Long-Term and Acute)

Refer to Section 11: Toxicological Information

Indication of any Immediate Medical Attention or Special Treatment Needs

Individuals with known allergies to sulfide drugs may also have allergic reactions to elemental sulfur

SECTION 5: FIREFIGHTING MEASURES				
Suitable Extinguishing Media	Water fog, spray, or regular foam. Do not use a direct water stream.			
Unsuitable Extinguishing Media	Do not use solid streams of water, which could create sulfur dust clouds and cause an explosion or could move burning sulfur to adjacent areas.			
Exposure Hazards	Prevent human exposure to smoke, fumes, or products of combustion (sulfur oxi gases). Evacuate nonessential personnel from the fire area. If large fire, evacuate peop downwind from fire. Consider evacuation for ½ mile in all directions.			
Advice for Firefighters	Firemen exposed to contaminated smoke should be immediately relieved and checked for symptoms of exposure of toxic gases. This should not be mistaken for heat exhaustion or smoke inhalation. Seek medical attention immediately!			
Protective Equipment	Wear full-faced, self-contained breathing apparatus and full protective clothing.			
Fire and Explosion Hazards	Fire will rekindle until mass is cooled below 310°F (154°C). Cool surrounding areas with water fog to prevent re-igniting. Sulfur dust is HIGHLY FLAMMABLE. If suspended in air, it will ignite by friction, static electricity, heat, sparks, or flames. Sulfur dust clouds may explode.			
Combustion Products	Sulfur oxide gases			

	SECTION 6: ACCIDENTAL RELEASE MEASURES
Personal Precautions	Minor spills such as torn or ruptured containers should be repaired or patched with tape if possible. Place spilled material in a disposable container. Avoid getting dust in eyes.
Protective Equipment	Maintain adequate ventilation. Wear a dust mask when dust is present or a respirator if smoke is present. Wear safety glasses.
Emergency Procedures	As an immediate precautionary measure isolate spills or leak areas. Eliminate all sources of ignition, such as flares, sparks, or flames, in the immediate area. No smoking. Ventilate closed spaces before entering.
Environmental Precautions	Do not allow runoff to enter lakes or waterways.
Containment/Cleanup Measures	Gently sweep or shovel up spilled material using a natural fiber broom and/or aluminum shovel to prevent sparking, to avoid creating a dust cloud. Place sweepings in an appropriate chemical waste container for reclaiming or disposal in an approved facility. Wash spill site after clean-up is complete.

SECTION 7: STORAGE AND HANDLING					
no go ig re	All handling and conveying equipment should be properly grounded and bonded. Be careful not to create dust. Avoid any conditions that might tend to create a dust explosion. Maintain good housekeeping practices to minimize dust build-up and dispersion. Eliminate sources of ignition. Keep away from heat, sparks, and flames. Use nonferrous tools, when available, to reduce sparking. Gently sweep or shovel up spilled materials using a natural fiber broom and/or aluminum shovel to prevent sparking. Maintain adequate ventilation in all areas.				
Co St ch	Conditions for Safe Storage, Including any Incompatibilities: Containers should be stored in a cool, dry, well-ventilated area. Keep container tightly close Store away from flammable materials, sources of heat, flames, and sparks. Separate fro chlorates, nitrates, and other oxidizing agents. Exercise due caution to prevent damage to leakage from container.				
-	eep away from flammable materials, sources of heat, flame, sparks, chlorates, nitrates and ther oxidizing agents.				
SECTION	8: EXPOSURE CONTROLS/ PERSONAL PROTECTION				
Engineering Measures/Controls	Maintain adequate ventilation in all areas. No flares or flames in area. Be careful not to create dust. Eliminate sources of ignition.				
Personal Protective Equipment					
Pictograms					
Respiratory	Wear dust masks and use NIOSH/MSHA approved dust respirator if airborne concentrations exceed exposure limits.				
Eyes/Face	Wear suitable, protective safety glasses to prevent eye irritation from dust.				
Hands	Wash hands thoroughly after handling and before eating or smoking.				
Skin/Body	Wear suitable, protective clothing to prevent skin irritation from dust. Wash skin thoroughly after handling and before eating or smoking. Wash contaminated clothing separately before reuse.				
Environmental Exposure Controls	Follow best practice for site management and disposal of waste. Avoid release to the environment.				
General Industrial Hygiene Considera	ations Protective equipment should be used in any situation that may result in hazardous exposure. Maintain good housekeeping practices to minimize dust build-up and dispersion. Eliminate sources of ignition. Use nonferrous tools to reduce sparking. Sweep or shovel up spilled material using a natural fiber broom and/or aluminum shovel to prevent sparking. Maintain adequate ventilation in all areas.				

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Solid, powder form			
Appearance	Yellow powder			
Formula	S ₈ (Rhombic or monoclinic)			
Odor	Odorless, or faint odor of rotten eggs			
Odor Threshold	No data available			
рН	No data available			
Boiling Point	832° F (444° C)			
Melting/Freezing Point	118-120°C (244-248°F)			
Flash Point	207°C (405°F) Closed Cup			
Evaporation Rate	No data available			
Flammability	May form combustible dust concentrations in air			
Flammable/Explosion Limits	Upper: 6.38% (v) Lower: 0.17% (v)			
Vapor Pressure	8mmHg at 246°C (475°F) 1mmHg at 183.8°C (362.8°F)			
Vapor Density	No data available			
Purity	99.5% Min.			
Auto-Ignition Temperature	240°C (464°F)			
Decomposition Temperature	Does not decompose			
Viscosity	Not applicable			
Specific Gravity	2.07 @ 70° F			
Solubility in Water	Insoluble			
Bulk Density	Powder: 33-80 lbs. /ft ³			

SECTION 10: STABILITY AND REACTIVITY				
Chemical Stability	Stable			
Conditions to Avoid	Keep from heat sources, sparks, and open flames. Minimize dust generation and accumulation.			
Incompatible Materials	Strong oxidizing agents, copper, copper alloys, steel, chlorates, nitrates			
Possibility of Hazardous Reactions Oxidizing agents may react violently				
Hazardous Decomposition Oxides of sulfur gases produced by burning sulfur				
Products				
Hazardous Polymerization	Will not occur			

SECTION 11: TOXICOLOGICAL INFORMATION				
Likely Routes of Exposure	Inhalation, ingestion, skin contact, and eye contact			
Signs and Symptoms of Overexposure	Nose or throat irritation, coughing, chest discomfort, asthma, difficulty breathing, nausea, vomiting, stinging eye irritation, skin irritation, hives.			
Exposure Limits	No exposure limits have been established			
Acute Symptoms and Effects Inhalation	Prolonged inhalation may cause irritation of respiratory tract. Breathing of dust may aggravate asthma and other pulmonary diseases.			
Eye Contact	Sulfur dust is an eye irritant.			
Skin Contact	No adverse effects; however, skin irritation may be aggravated in persons with existing skin lesions.			
Ingestion	Ingested sulfur is converted to sulfides in the gastrointestinal tract, and ingestion of 10 to 20 grams has caused irritation of the GI tract and renal injury. Swallowing large amounts may cause nausea and vomiting.			

		SECTION 11:	TOXICOLOGICAL IN	FORMATION (CON	IT)
Long-T	erm Effects	None know	n to humans		•
Toxicity		LD ₅₀ LC ₅₀ Skin Eye	Slightly irritating (rat	g (rats) 5.49-mg/L air concentration	
	S	ensitization	Reproductive Effects	Developmental Effects	Endocrine Disruptor
	No	t Established	Not Established	Not Established	Not Established
	<u> </u>	Carcinogenicity	Terat	togenicity	Mutagenicity
	This product	does not contain any in	gredient designated by NTP	, IARC, or OSHA as a proba	ble human carcinogen.
		SECTIC	N 12: ECOLOGICAL		
ToxicityToxicity to fishLC50- OncorhynchusLC50- other fish- 866		s mykiss (rainbow trout) -> 5 mg/l -96h na (Water flea) -> 5,000 mg			
Mobilit Degrad Bioacco Results	cotoxicityNo data availablelobilityNo data availableegradationNo data availableioaccumulationNo data availableesults of PBT andPBT/vPvB assessment not available as chemical safety assessment not required/not conductedPvB assessmentPVB assessment				uired/not conducted
		SECTIO	N 13. DISPOSAL CC	NSIDERATIONS	
	Treatment Met t Waste		nd/or container in accorda	nce with local, regional, na	tional, and/or international

Packaging Waste Dispose of content and/or container in accordance with local, regional, national and/or international regulations.

SECTION 14: TRANSPORTATION INFORMATION

Solid sulfur is not regulated if transported in non-bulk packaging (less than 400kg per package) or if formed to a specific shape, such as prills, granules, pellets, pastilles, or flakes (49 CFR 172.102, special provision 30).

US and Canadian Shipments

Bulk containers (packaging) of powdered sulfur of more than 400 kg (880 lbs.) per package

regulations.

	14.1 UN	14.2 UN proper	14.3 transport hazard	14.4 packaging	14.5 environmental
	number	shipping name	class(es)	group	hazards
DOT	NA1350	Sulfur (Sulphur)	9 (Misc. Hazardous	III	No data available
(Domestic)			Materials)		
DOT	UN1350	Sulphur (Sulfur)	4	III	No data available
(International)					
TDG	UN 1350	Sulfur	4.1	III	No data available

SECTION 14: TRANSPORTATION INFORMATION (CONT)

Other than US and Canadian Shipments

All shipments of powdered sulfur

IMO/IMDG	UN1350	Sulphur (Sulfur)	4.1 (flammable solid)		No data available
IATA/ICAO	UN1350	Sulfur	4.1	III	No data available

This product is not a Marine Pollutant as defined in 40 CFR Part 172.

Pictograms for Hazard Classes

Powdered sulfur packaging over 400 kg (880 lbs.) only



Special Precautions for User

None specified

	SECTION 15: REGULATORY INFORMATION				
TSCA	This product is listed on the TSCA Inventory at CAS Registry Number 7704-34-9.				
CERCLA	 Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) If this product is accidentally spilled, it is not subject to any special reporting. We recommend that you contact state and local authorities to determine if there are other local reporting requirements. 				
SARA TITLE III	Superfund Amendments and Reauthorization Act, Title III				
	• Sections 311/312: None. Section 313: None. Section 302: None.				
RCRA	Resource Conservation and Recovery Act				
	• Not subject to reporting because sulfur is not identified as a hazardous waste.				
SECTION 16: OTHER INFORMATION					
Last Revision Date	03/28/2019 Preparation Date 05/01/2015				
Additional Information	For additional information, contact your technical sales representative. For additional health and safety information, call Georgia Gulf Sulfur Corporation at 229-244-0000.				
Disclaimer/ Statement of Liability	THE INFORMATION CONTAINED HEREIN IS BASED ON THE PRESENT KNOWLEDGE AND DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. HOWEVER, INTERNATIONAL SULPHUR.				