

Therminol® VP1 Heat Transfer Fluid

Version 1.3 PRD

Revision Date: 02/27/2020

SDS Number: 150000093459 SDSUS / Z8 / 0001 Date of last issue: 12/04/2018 Date of first issue: 09/06/2016

SECTION 1. IDENTIFICATION

Product name

Therminol® VP1 Heat Transfer Fluid

Product code 34152-00, P3415203, P3415202, P3415200, E3415201

Manufacturer or supplier's details

Company name of supplier

: Eastman Chemical Company

Address 200 South Wilcox Drive

Kingsport TN 37660-5280

Telephone (423) 229-2000

Emergency telephone CHEMTREC: +1-800-424-9300, +1-703-527-3887 CCN7321

Recommended use of the chemical and restrictions on use

Recommended use

Heat transfer fluids

Restrictions on use None known.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Acute toxicity (Inhalation) : Category 4

Skin irritation Category 2

- single exposure

Specific target organ toxicity : Category 3 (Respiratory system)

GHS label elements

Hazard pictograms

Signal Word Warning

Hazard Statements H315 Causes skin irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

Precautionary Statements

Prevention:



Therminol® VP1 Heat Transfer Fluid

Version 1.3 PRD Revision Date: 02/27/2020

SDS Number: 150000093459 SDSUS / Z8 / 0001 Date of last issue: 12/04/2018 Date of first issue: 09/06/2016

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON

and keep cominitable for breathing. Call a P

CENTER/doctor if you feel unwell.

P332 + P313 If skin irritation occurs: Get medical advice/ atten-

tion.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components

•		
Chemical name	CAS-No.	Concentration (% w/w)
diphenyl oxide	101-84-8	73.5
Biphenyl; diphenyl	92-52-4	26.5

SECTION 4. FIRST AID MEASURES

If inhaled : Remove person to fresh air and keep comfortable for

breathing.

If breathing is difficult, give oxygen. Consult a physician if necessary.

In case of skin contact : Wash off immediately with soap and plenty of water while

removing all contaminated clothes and shoes. If skin irritation occurs: Get medical advice/ attention.

Wash contaminated clothing before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

Get medical attention if symptoms occur.

If swallowed : IF SWALLOWED: Immediately call a POISON

CENTER/doctor.

Do NOT induce vomiting.

Rinse mouth.



Therminol® VP1 Heat Transfer Fluid

Version 1.3 PRD Revision Date: 02/27/2020

SDS Number: 150000093459 SDSUS / Z8 / 0001 Date of last issue: 12/04/2018 Date of first issue: 09/06/2016

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

Causes skin irritation. Harmful if inhaled.

May cause respiratory irritation.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Carbon dioxide (CO2)

Dry chemical

Foam

Unsuitable extinguishing

media

Do not use a solid water stream as it may scatter and spread

fire.

Hazardous combustion prod-

ucts

Hazardous decomposition products due to incomplete

combustion Carbon oxides

Further information : Use a water spray to cool fully closed containers.

Do not allow run-off from fire fighting to enter drains or water

courses.

This product is not classified as a fire-resistant heat transfer fluid. Precautions to avoid sources of ignitions should be

taken.

Special protective equipment

for fire-fighters

Wear an approved positive pressure self-contained breathing

apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Ventilate the area.

Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

Avoid contact with skin and eyes.

Material can create slippery conditions.

Wear appropriate personal protective equipment.

Local authorities should be advised if significant spillages

cannot be contained.

Environmental precautions : Clear up spills immediately and dispose of waste safely.

Avoid release to the environment.

Collect spillage.

Methods and materials for containment and cleaning up

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local /



Version Revision Date: SDS Number: Date of last issue: 12/04/2018 1.3 02/27/2020 150000093459 Date of first issue: 09/06/2016

PRD SDSUS / Z8 / 0001

national regulations (see section 13).

Prevent runoff from entering drains, sewers, or streams.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapors or spray mist.

Handle product only in closed system or provide appropriate

exhaust ventilation at machinery.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Keep away from flames and sparks.

Wear appropriate personal protective equipment.

Avoid contact with skin, eyes and clothing.

Wash thoroughly after handling.

Wash contaminated clothing before reuse.

Drain or remove substance from equipment prior to break-in

or maintenance.

Handle in accordance with good industrial hygiene and safety

practice.

Conditions for safe storage : Store locked up.

Keep container tightly closed in a dry and well-ventilated

place.

Keep in a cool place away from oxidizing agents.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
diphenyl oxide	101-84-8	TWA (Vapor)	1 ppm	ACGIH
		STEL (Va- por)	2 ppm	ACGIH
		TWA (Vapor)	1 ppm 7 mg/m3	NIOSH REL
		TWA (Vapor)	1 ppm 7 mg/m3	OSHA Z-1
		TWA (Vapor)	1 ppm 7 mg/m3	OSHA P0
Biphenyl; diphenyl	92-52-4	TWA	0.2 ppm	ACGIH
		TWA	0.2 ppm 1 mg/m3	NIOSH REL
		TWA	0.2 ppm 1 mg/m3	OSHA Z-1
		TWA	0.2 ppm 1 mg/m3	OSHA P0



Version 1.3 PRD

Revision Date: 02/27/2020

SDS Number: 150000093459 SDSUS / Z8 / 0001 Date of last issue: 12/04/2018 Date of first issue: 09/06/2016

Engineering measures

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protective equipment

Respiratory protection

Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this

is necessary.

Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable.

If engineering controls do not maintain airborne

concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved

respirator must be worn.

Hand protection

Remarks Wear suitable gloves. When handling hot material, use heat

resistant gloves.

Eve protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear suitable protective clothing.

Protective measures Ensure that eye flushing systems and safety showers are

located close to the working place.

Handle in accordance with good industrial hygiene and safety Hygiene measures

practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

liquid

Color colorless

Odor characteristic

Odor Threshold not determined



Therminol® VP1 Heat Transfer Fluid

Version 1.3 PRD

Revision Date: 02/27/2020

SDS Number: 150000093459 SDSUS / Z8 / 0001 Date of last issue: 12/04/2018 Date of first issue: 09/06/2016

pΗ

not determined

Melting point/range 54 °F / 12 °C

495 °F / 257 °C Boiling point/boiling range

(1,013 hPa)

230 °F / 110 °C Flash point

Method: Pensky-Martens closed cup

255 °F / 124 °C

Method: Cleveland open cup

not determined Evaporation rate

1150 °F / 621 °C Self-ignition

Method: ASTM D2155

Vapor pressure not determined

Relative vapor density not determined

Relative density 1.06 (77 °F / 25 °C)

Density 1,060 kg/m3 (77 °F / 25 °C)

Solubility(ies)

Water solubility 0.025 g/l

Partition coefficient: n-

octanol/water

Not applicable

not determined Autoignition temperature

Decomposition temperature not determined

Viscosity Viscosity, dynamic

not determined

2.48 mm2/s (104 °F / 40 °C) Viscosity, kinematic

0.99 mm2/s (212 °F / 100 °C)

Not classified Explosive properties

Oxidizing properties Not classified



Therminol® VP1 Heat Transfer Fluid

Version 1.3

PRD

Revision Date: 02/27/2020

SDS Number: 150000093459 SDSUS / Z8 / 0001 Date of last issue: 12/04/2018 Date of first issue: 09/06/2016

SECTION 10. STABILITY AND REACTIVITY

Reactivity : None reasonably foreseeable.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

: None known.

Conditions to avoid : Heating in air.

Keep away from flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

: Emits acrid smoke and fumes when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if inhaled.

Product:

Acute oral toxicity

: LD50 Oral (Rat): 2,050 mg/kg

Assessment: May be harmful if swallowed.

Acute inhalation toxicity : LC50 (Rat, male and female): 2.66 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Assessment: Harmful if inhaled.

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,010 mg/kg

Assessment: Not classified

Components:

diphenyl oxide:

Acute oral toxicity

: LD50 Oral (Rat, female): 2,830 mg/kg

Acute inhalation toxicity : LC50: Remarks: No data available

Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): > 7,940 mg/kg

Biphenyl; diphenyl:

Acute oral toxicity

: LD50 Oral (Rat, male): > 2,180 mg/kg

Assessment: The component/mixture is minimally toxic after

single ingestion.



Therminol® VP1 Heat Transfer Fluid

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/04/2018

 1.3
 02/27/2020
 150000093459
 Date of first issue: 09/06/2016

PRD SDSUS / Z8 / 0001

Acute inhalation toxicity : LC50 (Rat, male and female): > 3.47 mg/l

Exposure time: 1 h

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Skin corrosion/irritation

Causes skin irritation.

Product:

Species : Rabbit Exposure time : 24 h

Assessment : Causes skin irritation.

Result : slight

Components:

diphenyl oxide:

Species : Rabbit Exposure time : 4 h Result : none

Biphenyl; diphenyl:

Species : Rabbit Result : slight

Species : Humans

Assessment : Irritating to skin.

Result : strong

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Species : Rabbit

Result : No eye irritation

Exposure time : 24 h

Assessment : Not classified

Components:

diphenyl oxide:

Species : Rabbit

Result : corneal opacity

Exposure time : 4 h
Assessment : irritating

Result : slight to moderate

Biphenyl; diphenyl:

Species : Rabbit

Result : slight irritation



Therminol® VP1 Heat Transfer Fluid

Version Revision Date: SDS Number: Date of last issue: 12/04/2018 1.3 02/27/2020 150000093459 Date of first issue: 09/06/2016

PRD SDSUS / Z8 / 0001

Species : Humans Result : strong

Assessment : Irritating to eyes.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : No data available

Components:

diphenyl oxide:

Test Type : Skin Sensitization Species : Guinea pig Assessment : Not classified

Method : OECD 406: Guinea pig sensitization

Result : non-sensitizing

Test Type : Human experience

Species : Humans Assessment : Not classified

Method : Human Repeat Insult Patch Test

Result : non-sensitizing

Biphenyl; diphenyl:

Test Type : OECD 406: Guinea pig sensitization

Species : Guinea pig
Assessment : Not classified

Result : Does not cause skin sensitization.

Germ cell mutagenicity

Not classified based on available information.

Product:

Genotoxicity in vitro : Test Type: Salmonella typhimurium assay (Ames test)

Metabolic activation: +/- activation

Method: Bacterial Reverse Mutation Assay

Result: negative

Test Type: Chromosome aberration test in vitro

Metabolic activation: +/- activation

Method: In vitro Mammalian Chromosome Aberration Test

Result: negative

Genotoxicity in vivo : Test Type: Mammalian Erythrocyte Micronucleus Test

Species: Mouse

Method: Mammalian Erythrocyte Micronucleus Test



Therminol® VP1 Heat Transfer Fluid

Version 1.3 Revision Date: 02/27/2020

SDS Number: 150000093459 SDSUS / Z8 / 0001 Date of last issue: 12/04/2018 Date of first issue: 09/06/2016

Result: negative

Components:

diphenyl oxide: Genotoxicity in vitro

: Test Type: Salmonella typhimurium assay (Ames test)

Metabolic activation: +/- activation

Method: Bacterial Reverse Mutation Assay

Result: negative

Test Type: Mutagenicity - Mammalian Metabolic activation: +/- activation

Method: In vitro Mammalian Cell Gene Mutation Test

Result: negative

Test Type: Mutagenicity - Mammalian Metabolic activation: +/- activation

Method: In vitro Mammalian Chromosome Aberration Test

Result: negative

Test Type: Mutagenicity - Mammalian Metabolic activation: +/- activation Method: OECD Guideline 482

Result: negative

Biphenyl; diphenyl:

Genotoxicity in vitro

: Test Type: Salmonella typhimurium assay (Ames test)

Metabolic activation: +/- activation

Method: Bacterial Reverse Mutation Assay

Result: negative

Test Type: Mutagenicity - Mammalian Metabolic activation: + activation

Method: In vitro Mammalian Cell Gene Mutation Test

Result: positive

Test Type: Chromosome aberration test in vitro

Metabolic activation: +/- activation

Method: In vitro Mammalian Chromosome Aberration Test

Result: negative

Test Type: Mutagenicity - Mammalian

Method: OECD Guideline 482

Result: negative

Genotoxicity in vivo : Species: Mouse (male and female)

Method: Mammalian Erythrocyte Micronucleus Test

Result: negative

Species: Rat (male)

Method: Mammalian Bone Marrow Chromosome Aberration



Therminol® VP1 Heat Transfer Fluid

Version Revision Date: SDS Number: Date of last issue: 12/04/2018 150000093459 Date of first issue: 09/06/2016 1.3 02/27/2020

SDSUS / Z8 / 0001 PRD

Test

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Biphenyl; diphenyl:

Species Rat, male and female

Application Route Ingestion

OECD Test No. 453: Combined Chronic Toxici-Method

ty/Carcinogenicity Studies

Remarks Expert judgment

Not classified

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Product:

Effects on fertility

Remarks: No data available

Components:

diphenyl oxide:

Reproductive toxicity - As-

sessment

Based on available data the classification criteria are not met.

Not classified as hazardous.

Biphenyl; diphenyl:

Effects on fetal development Species: Rabbit, female

Application Route: Oral

General Toxicity Maternal: NOAEL: 3,000 ppm Embryo-fetal toxicity.: NOAEL: 8.000 ppm

Method: OECD Test Guideline 414

Species: Rat

Application Route: Oral

General Toxicity Maternal: NOAEL: 500 mg/kg body weight Embryo-fetal toxicity.: NOAEL: 1,000 mg/kg body weight

Method: OECD Test Guideline 414

Reproductive toxicity - As-Based on available data the classification criteria are not met.



Therminol® VP1 Heat Transfer Fluid

Version Revision Date: SDS Number: Date of last issue: 12/04/2018 1.3 02/27/2020 150000093459 Date of first issue: 09/06/2016

PRD SDSUS / Z8 / 0001

sessment Not classified as hazardous.

STOT-single exposure

May cause respiratory irritation.

Product:

Routes of exposure : Inhalation

Assessment : Irritating to respiratory system.

Components:

diphenyl oxide:

Routes of exposure : Inhalation

Assessment : Based on available data, the classification criteria are not met.

Biphenyl; diphenyl:

Routes of exposure : Inhalation

Target Organs : Respiratory system

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 3 with respiratory tract

irritation.

STOT-repeated exposure

Not classified based on available information.

Product:

Routes of exposure : Oral

Assessment : Not classified

Components:

diphenyl oxide:

Assessment : Based on available data, the classification criteria are not met.

Biphenyl; diphenyl:

Target Organs : Kidney, Liver, Urinary bladder

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Repeated dose toxicity

Product:

Species : Rat, male and female

0.051 mg/l

Application Route : Inhalation study:

Exposure time : 90 days

Species : Rat LOAEL : 500 mg/l Application Route : by gavage



Therminol® VP1 Heat Transfer Fluid

Version Revision Date: SDS Number: Date of last issue: 12/04/2018 1.3 02/27/2020 150000093459 Date of first issue: 09/06/2016

PRD SDSUS / Z8 / 0001

Components:

diphenyl oxide:

Species : Rat, male and female

NOAEL : 301 mg/kg Application Route : Oral Study Exposure time : 90 days

Remarks : (highest dose tested)

Species : Rat, male and female

NOAEL : 1000 mg/kg
Application Route : Dermal Study
Exposure time : 90 days

Remarks : (highest dose tested)

Species : Rat, male and female

NOAEL : 139 mg/m3
Application Route : inhalation (vapor)

Exposure time : 28 days

Remarks : (highest dose tested)

Biphenyl; diphenyl:

Species : Rat, male and female

NOAEL : 39 mg/kg Application Route : in feed Exposure time : 2 year

Method : OECD Test No. 453: Combined Chronic Toxici-

ty/Carcinogenicity Studies

Target Organs : Blood, Kidney, Liver

Species : Rabbit

NOAEL : > 2,000 mg/kg

Application Route : Dermal Exposure time : 28 days

Remarks : No significant adverse effects were reported

Aspiration toxicity

Not classified based on available information.

Product:

Not classified

Information on likely routes of exposure

Product:

Inhalation : Remarks: Harmful if inhaled.

May cause respiratory irritation.

Skin contact : Remarks: Causes skin irritation.

Eye contact : Remarks: None known.



Therminol® VP1 Heat Transfer Fluid

Version 1.3 Revision Date: 02/27/2020

SDS Number: 150000093459 SDSUS / Z8 / 0001 Date of last issue: 12/04/2018 Date of first issue: 09/06/2016

Ingestion

Remarks: May be harmful if swallowed.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 7.6 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): 2.4 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Selenastrum capricornutum (green algae)): 1.3 mg/l

Exposure time: 72 h

Components:

diphenyl oxide:

Toxicity to fish

: LC50 (Oncorhynchus mykiss (rainbow trout)): 4.2 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): 1.7 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (algae)): 0.455 mg/l

Exposure time: 72 h

Biphenyl; diphenyl:

Toxicity to fish

EC50 (Pimephales promelas (fathead minnow)): 3 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.36 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Chlorella pyrenoidosa): 1.3 mg/l

Exposure time: 72 h

NOEC (Chlorella pyrenoidosa): 0.66 mg/l

Exposure time: 72 h

M-Factor (Acute aquatic tox- :

icity)

: 1

Toxicity to fish (Chronic tox-

icity)

NOEC (Oncorhynchus mykiss (rainbow trout)): 0.229 mg/l

Exposure time: 96 d

Toxicity to daphnia and other aquatic invertebrates (Chron-

NOEC (Daphnia magna (Water flea)): 0.17 mg/l

Exposure time: 21 d



Therminol® VP1 Heat Transfer Fluid

Version 1.3 PRD Revision Date: 02/27/2020

SDS Number: 150000093459 SDSUS / Z8 / 0001 Date of last issue: 12/04/2018 Date of first issue: 09/06/2016

ic toxicity)

M-Factor (Chronic aquatic

toxicity)

: 1

Persistence and degradability

Product:

Biodegradability

Result: Inherently biodegradable.

Method: Inherent Biodegradability: Modified SCAS Test

Biochemical Oxygen De-

mand (BOD)

Remarks: No data available

Chemical Oxygen Demand

(COD)

Remarks: No data available

BOD/COD : Remarks: No data available

Components:

diphenyl oxide:

Biodegradability

: Result: Readily biodegradable.

Method: Ready Biodegradability: Modified MITI Test (I)

Biochemical Oxygen De-

mand (BOD)

Remarks: No data available

Chemical Oxygen Demand

(COD)

Remarks: No data available

Biphenyl; diphenyl:

Biodegradability

Result: Readily biodegradable.

Method: Ready Biodegradability: Modified MITI Test (I)

Bioaccumulative potential

Components:

diphenyl oxide: Bioaccumulation

. c

Species: Cyprinus carpio (Carp)

Bioconcentration factor (BCF): 49 - 594 Method: OECD Test Guideline 305

Species: Oncorhynchus mykiss (rainbow trout)

Bioconcentration factor (BCF): 196



Therminol® VP1 Heat Transfer Fluid

Version 1.3 PRD Revision Date: 02/27/2020

SDS Number: 150000093459 SDSUS / Z8 / 0001 Date of last issue: 12/04/2018 Date of first issue: 09/06/2016

Biphenyl; diphenyl:

Bioaccumulation

: Bioconcentration factor (BCF): 1,900

Mobility in soil

Components:

diphenyl oxide:

Distribution among environmental compartments Koc: 1960, log Koc: 3.3

Biphenyl; diphenyl:

Distribution among environ-

mental compartments

Medium: Soil

Koc: 1546, log Koc: 3.19

Method: OECD Test No. 106: Adsorption - Desorption Using a

Batch Equilibrium Method

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

This material when discarded may be a hazardous waste as that term is defined by the Resource Conservation and Recovery Act (RCRA), 40 CFR 261.24, due to its toxicity characteristic. This material should be analyzed in accordance with Method 1311 for the compound D018

BENZENE.

Consult 40 CFR 268.40 or appropriate local regulations for

concentration based standards.

This product meets the criteria for a synthetic used oil under the U.S. EPA Standards for the Management of Used Oil (40 CFR 279). Those standards govern recycling and disposal in lieu of 40 CFR 260 -272 of the Federal hazardous waste

program in states that have adopted these used oil

regulations. Consult your attorney or appropriate regulatory official to be sure these standards have been adopted in your state. Recycle or burn in accordance with the applicable

standards.

Eastman Chemical Company operates a used fluid return program for certain fluids under these used oil standards.

Contact your Sales Representative for details.



Version Revision Date: SDS Number: Date of last issue: 12/04/2018 Date of first issue: 09/06/2016 1.3 02/27/2020 150000093459

PRD SDSUS / Z8 / 0001

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. UN 3082

Proper shipping name Environmentally hazardous substance, liquid, n.o.s.

(Diphenyl Ether, biphenyl)

9 Class Packing group Ш

Class 9 - Miscellaneous dangerous substances and articles Labels

Packing instruction (cargo 964

aircraft)

Packing instruction (passen-

964 ger aircraft)

Remarks Shipping in package sizes of less than 5 L (liquids) or 5 KG

(solids) may lead to a non-regulated classification.

IMDG-Code

UN number UN 3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Diphenyl Ether, biphenyl, diphenyl)

Class 9 Ш Packing group Labels 9 EmS Code F-A, S-F yes Marine pollutant

Shipping in package sizes of less than 5 L (liquids) or 5 KG Remarks

(solids) may lead to a non-regulated classification.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number UN 3082

Proper shipping name Environmentally hazardous substance, liquid, n.o.s.

(biphenyl)

Class 9 Ш Packing group

Labels Class 9 - Miscellaneous dangerous substances and articles

ERG Code

Marine pollutant yes(diphenyl)

Remarks Shipping in package sizes of less than 5 L (liquids) or 5 KG

(solids) may lead to a non-regulated classification.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.



Version Revision Date: SDS Number: Date of last issue: 12/04/2018 1.3 02/27/2020 150000093459 Date of first issue: 09/06/2016

PRD SDSUS / Z8 / 0001

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ Calculated product R0	
		(lbs)	(lbs)
Biphenyl; diphenyl	92-52-4	100	377

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards

: Acute toxicity (any route of exposure)

Skin corrosion or irritation

Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Biphenyl; diphe- 92-52-4

nyl

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

The ingredients of this product are reported in the following inventories:

TCSI

: On the inventory, or in compliance with the inventory

AICS : On the inventory, or in compliance with the inventory

DSL : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

ISHL : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/04/2018

 1.3
 02/27/2020
 150000093459
 Date of first issue: 09/06/2016

PRD SDSUS / Z8 / 0001

TSCA list


No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA PO : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/04/2018

 1.3
 02/27/2020
 150000093459
 Date of first issue: 09/06/2016

 PRD
 SDSUS / Z8/0001

- International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China: IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship: RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG -United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to

compile the Material Safety

Data Sheet

Revision Date : 02/27/2020

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

: www.therminol.com/products/

US / Z8